



Product Data Sheet

| | <u>United States Units</u> | <u>Metric Units</u> | <u>Test Method</u> |
|--------------------------------|----------------------------|---------------------|--------------------|
| <i>Backing</i> | | | |
| <i>Adhesive</i> | | | |
| <i>Total Thickness</i> | | | |
| <i>Film Thickness</i> | | | |
| <i>Adhesive Thickness</i> | | | |
| <i>Adhesion to Steel</i> | | | |
| <i>Tensile Strength</i> | | | |
| <i>Initial Tack</i> | | | PSTC-16 |
| <i>Holding Power</i> | | | ASTM D3654 |
| <i>Elongation</i> | | | |
| <i>Service Temperature</i> | | | |
| <i>Application Temperature</i> | | | |

Storage Conditions

Store in a clean, dry place at room temperature.
Avoid temperature and humidity extremes.

Safety/Environmental Information:

MSDS Class:
Health:
Fire:
Reactivity:
VOC:
CONEG:

Hazard Ratings: 0 - Minimal, 1 - Slight, 2 - Moderate, 3 - Serious, 4 - Extreme

Does not contain any substances according to the Ozone Depleting Substances, 40 CFR Part 82 and the Safe Drinking Water Enforcement Act of 1986.

Important Notice: All properties are approximate and based on calculations and tests we believe to be reliable. However, the accuracy and completeness are not guaranteed. Before using, user shall determine the suitability of the product for its own use and assumes all risk and liability related to the product. The seller limits its obligations to replacement or at its option, reimbursement of the purchase price of products shown to the seller's satisfaction to have been defective at the time the seller sold it.