



DC612

Double Sided Tape

Double Sided Paper Tape	
Flatback paper coated with solvent-based synthetic rubber adhesive that offers high shear strength and moderate adhesion. It has aggressive tack and provides excellent bonding to low surface energy substrates.	
Backing	Flatback Paper
Adhesive	Synthetic Solvent Rubber
Total Thickness with Release Liner	10.5 mil (White Glassine Liner)
Total Thickness without Release Liner	7.0 mil
Adhesion to Steel	56 oz/in
Tensile Strength	25 lb/in width
Elongation	2% at break
Service Temperature:	-4 °F ~ 140 °F (-20 °C ~ 60 °C)
Storage Conditions	Store in a clean, dry place at room temperature. Avoid temperature and humidity extremes.
Suitable for photography mounting, carpet installation, steel-rule die, textile manufacturing (twister room), printing industry, and sports application (e.g. golf grips, bike grips)	
Important Notice: The above listed information is based on calculations and tests we believe to be reliable. However, the accuracy and completeness are not guaranteed. Before using, user shall determine the suitability of the product for its own use and assumes all risk and liability related to the product. The seller limits its obligations to replacement or at its option, reimbursement of the purchase price of products shown to the seller's satisfaction to have been defective at the time the seller sold it.	