



# DF2CW

Double Sided PE Foam

## Product Information

### Description

QSPAC® DF2CW is a 1/8" thick double sided white PE foam tape, which features a closed-cell, irradiation cross-linked PE foam as the carrier, and a high performing, solvent based pressure sensitive acrylic adhesive, with a 120 gram/M<sup>2</sup> PE coated white paper liner.

QSPAC® DF2CW is a general-purpose product, with excellent adhesion to various surfaces and good holding power. It is opaque white, long lasting, UV, moisture and solvent resistant, and easy to apply.

### Applications

- General purpose for mounting, sealing, and cushioning applications
- Good for bonding to various surfaces, indoor and outdoor, such as sign mounting

Property	Metric	Imperial	Test Standard
THICKNESS	3.0 mm	1/8 inch	PSTC-133
ADHESIVE THICKNESS	60 um each side	2.4 mil	PSTC-133
ADHESION TO STEEL	≥ 8.0 N/cm	≥ 72 oz/inch	PSTC-101, C
INITIAL TACK	≤ 50 mm	≤ 2.0 inch	PSTC-6
HOLDING POWER	≥ 2,880 minute, 23 °C	≥ 2,880 minute, 73 °F	PSTC-107
FOAM DENSITY	65 kg/M <sup>3</sup>	4.0 lb/ft <sup>3</sup>	-
ELONGATION	250 %		PSTC-131

### Storage Conditions

To obtain best performance, use this product within two years from date of manufacture, while stored in the original packaging in room condition under 23 °C (73 °F) and 50 % relative humidity.

### Standard Dimension of Jumbo Roll

1,040 mm (usable 1,020 mm) x 104 M

**DISCLAIMER:** All properties are approximate and based on calculations and tests we believe to be reliable. However, the accuracy and completeness are not guaranteed. Before using, user shall determine the suitability of the product for its own use and assumes all risk and liability related to the product. The seller limits its obligations to replacement or at its option, reimbursement of the purchase price of products shown to the seller's satisfaction to have been defective at the time the seller sold it.

[www.QSPAC.com](http://www.QSPAC.com)