



DL14C

Double Sided PET Film

Product Information

Description

Qspac® DL14C is a 4.4 mil double sided PET film tape, with a solvent based, pressure sensitive acrylic adhesive, and a 120 gram/M² (73#) PE coated white paper liner.

Qspac® DL14C features high tack and adhesion, so it is good for various foams, felts and fabrics lamination. It is clear, long lasting, hand tear-able, UV, moisture and solvent resistant, and easy to apply.

Applications

- Lamination, splicing and holding of film, foam, paper and other common flexible materials
- General purpose, good for foams, felts and fabrics applications

Property	Metric	Imperial	Test Standard
Thickness	110 µm	4.4 mil	PSTC-133
Adhesion to Steel	7.2 N/cm	65 oz/inch	PSTC-101, C
Initial Tack	≤ 120 mm	≤ 4.7 inch	PSTC-6
Holding Power	≥ 30 minute, 23 °C	≥ 30 minute, 73 °F	PSTC-107
Tensile Strength	19.6 N/cm	11.0 lb/inch	PSTC-131
Heat Resistance	60 °C	140 °F	-
Elongation	150 %		PSTC-131

Storage Conditions

To obtain best performance, use this product within two years from date of manufacture, while stored in the original packaging in room condition under 23 °C (73 °F) and 50 % relative humidity.

Standard Dimension of Jumbo Rolls

1,260 mm (usable 1,240 mm) x 1,000 M
1,400 mm (usable 1,380 mm) x 1,000 M

DISCLAIMER: All properties are approximate and based on calculations and tests we believe to be reliable. However, the accuracy and completeness are not guaranteed. Before using, user shall determine the suitability of the product for its own use and assumes all risk and liability related to the product. The seller limits its obligations to replacement or at its option, reimbursement of the purchase price of products shown to the seller's satisfaction to have been defective at the time the seller sold it.

www.QSPAC.com