



DS25L

Double Sided Tissue

Product Information

Description

Qspac® DS25L is a 5.2 mil double sided tissue tape, which features a great performing, solvent based pressure sensitive acrylic adhesive, with a high density 120 gram/M² PE coated white paper liner.

Qspac® DS25L is an industry oriented product, with good holding power, initial tack and peel adhesion. It is translucent, long lasting, hand tear-able, UV, moisture and solvent resistant, and easy to apply.

Applications

- Good for plastic and metal nameplates, membrane panel switches
- Corrugated paper splicing, paperboard, carton box fabrications
- Demanding utility and industrial applications

Property	Metric	Imperial	Test Standard
THICKNESS (Liner)	130 µm	5.2 mil (4.5 mil)	PSTC-133
ADHESION TO STEEL	≥ 13 N/25mm	≥ 47 oz/inch	PSTC-101, C
INITIAL TACK	≤ 120 mm	≤ 4.8 inch	PSTC-6
HOLDING POWER	≥ 600 minute, 23 °C	≥ 600 minute, 73 °F	PSTC-107
	≥ 10 minute, 80 °C	≥ 10 minute, 176 °F	-
TENSILE STRENGTH	9.8 N/25mm	5.5 lb/inch	PSTC-131
HEAT RESISTANCE	80 °C	176 °F	-
ELONGATION	5 %		PSTC-131

Storage Conditions

To obtain best performance, use this product within two years from date of manufacture, while stored in the original packaging in room condition under 23 °C (73 °F) and 50 % relative humidity.

Standard Dimension of Jumbo Roll

1,260 mm (usable 1,240 mm) x 1,000 M

DISCLAIMER: All properties are approximate and based on calculations and tests we believe to be reliable. However, the accuracy and completeness are not guaranteed. Before using, user shall determine the suitability of the product for its own use and assumes all risk and liability related to the product. The seller limits its obligations to replacement or at its option, reimbursement of the purchase price of products shown to the seller's satisfaction to have been defective at the time the seller sold it.

www.QSPAC.com