



# DT390

Duct Tape

<b>Utility Grade Duct Tape</b>	
PE Film tape with PET cloth reinforcement with an aggressive synthetic rubber pressure sensitive adhesive combined to provide a versatile utility tape which is conformable to irregular surfaces.	
Backing	LDPE film
Reinforcement	PET Cloth
Colors	Red, Silver
Adhesive	Synthetic Rubber
Total Thickness	9.0 mil
Adhesion to Steel	50 oz/in
Tensile Strength	20 lb/in width
Elongation	15 - 25% at break
Service Temperature	5°F to 158°F (- 15°C to 70°C)
Application Temperature	32°F to 95°F (- 0°C to 35°C)
Storage Conditions	Store in a clean, dry place at room temperature. Avoid temperature and humidity extremes.
Suitable for book repair, color coding, packaging, wrapping and sealing, bundling, and general maintenance.	
<small>Important Notice: The above listed information is based on calculations and tests we believe to be reliable. However, the accuracy and completeness are not guaranteed. Before using, user shall determine the suitability of the product for its own use and assumes all risk and liability related to the product. The seller limits its obligations to replacement or at its option, reimbursement of the purchase price of products shown to the seller's satisfaction to have been defective at the time the seller sold it.</small>	

12/09