



MK655

Masking Tape

14-Day Professional Painter's Masking Tape	
Professional painter's tape is specially designed for exposure to sunlight for up to 14 days, exhibiting secure adhesion and easy, clean removal from most surfaces. Conformable. Resistant to humidity and paint bleed-through.	
Backing	Smooth Crepe Paper
Color	Dark Blue
Adhesive	Solvent Based Natural Rubber
Total Thickness	5.2 mil
Adhesion to Steel	17.5 oz/in
Tensile Strength	25 lb/in width
Elongation	10% at break
Max. Temperature Resistance	203°F (95°C)
Max. Application Temperature	176°F (80°C)
Storage Conditions	Store in a clean, dry place at room temperature. Avoid temperature and humidity extremes.
Application	Suitable for wherever masking will be exposed to weather, outdoors conditions, interior masking of windows (where adhesive will be directly exposed to sunlight). Compatible for use on polyurethane-coated surfaces, unfinished wood, wallpaper or new, unpainted, or freshly painted wallboard. Caution: Blue color is a dye added to paper. Not recommended for use on lacquer.
Important Notice: The above listed information is based on calculations and tests we believe to be reliable. However, the accuracy and completeness are not guaranteed. Before using, user shall determine the suitability of the product for its own use and assumes all risk and liability related to the product. The seller limits its obligations to replacement or at its option, reimbursement of the purchase price of products shown to the seller's satisfaction to have been defective at the time the seller sold it.	