



MK664

Masking Tape

Performance Masking Tape

MK664 is an all around performance masking tape that is ideal for most industrial applications: either for high temperature resistance or for higher tensile strength requirements in paint masking and temporary object holding as well. With a relatively higher adhesion, it adheres well to various surfaces, and at the same time peels off cleanly without adhesive residue.

Natural color

Recommended for indoor applications only.

Backing	Crepe Paper
Adhesive	Solvent-based Natural Rubber
Total Thickness	6.4 mil (0.162 mm)
Adhesion to Steel (ASTM-D3330)	35 oz/in (3.9 N/10 mm)
Tensile Strength (ASTM-D3759)	24 lb/in width (43 N/10 mm)
Elongation (ASTM-D3759)	10 % at break
Maximum Temperature Resistance	230 °F/ 110 °C
Storage Conditions	Store in a clean, dry place at room temperature. Avoid temperature and humidity extremes.

Important Notice: The above listed information is based on calculations and tests we believe to be reliable. However, the accuracy and completeness are not guaranteed. Before using, user shall determine the suitability of the product for its own use and assumes all risk and liability related to the product. The seller limits its obligations to replacement or at its option, reimbursement of the purchase price of products shown to the seller's satisfaction to have been defective at the time the seller sold it.