



# PN820

Natural Rubber Carton Sealing Tape

<b>BOPP Tape for Carton Sealing coated with Solvent Natural Rubber Adhesive</b>	
For medium weight box sealing and packaging applications.	
Backing	Biaxially Oriented Polypropylene
Adhesive	Solvent Natural Rubber
Total Thickness	2.0 mil
Film Thickness	1.2 mil
Adhesive Thickness	0.8 mil
Adhesion to Steel	32 oz/in (8.8 N/25mm)
Tensile Strength	22 lb/in (98 N/25mm)
Elongation	140% at break
Application Temperature Range	32°F (0°C) to 122°F (50°C)
Operating Temperature Range	-30°F (-35°C) to 200°F (93°C)
Storage Conditions	Store in a clean, dry place at room temperature. Avoid temperature and humidity extremes.
<b>Safety / Environmental Information:</b>	
MSDS Class: S	Hazard Ratings:
Health: 1	0. Minimal
Fire: 0	1. Slight
Reactivity: 0	2. Moderate
VOC: N/A	3. Serious
CONEG: Complies	4. Extreme
Important Notice: The above listed information is based on calculations and tests we believe to be reliable. However, the accuracy and completeness are not guaranteed. Before using, user shall determine the suitability of the product for its own use and assumes all risk and liability related to the product. The seller limits its obligations to replacement or at its option, reimbursement of the purchase price of products shown to the seller's satisfaction to have been defective at the time the seller sold it.	

06/11