



SV265

Product Data Sheet

Striped Soft Vinyl Tape

A soft PVC film, color stripe printed, coated on one side with a rubber based pressure sensitive adhesive system. The tape is conformable and stretchy. It adheres well to all sorts of surfaces, resists abrasion, chemicals, acids, alkalis and moisture, and works well outdoors.

Applications: *Lane marking, color coding, safety warning*

	<i>Imperial</i>	<i>Metric</i>	<i>Test Method</i>
<i>Backing</i>	Plasticized and Stabilized PVC film		
<i>Adhesive</i>	Rubber Based		
<i>Total Thickness</i>	6.0 mil	0.15 mm	
<i>Adhesion to Steel</i>	18 oz/in	1.9 N/cm	ASTM D-1000
<i>Tensile Strength</i>	17 lb/in	34 N/cm	ASTM D-1000
<i>Elongation</i>	200 %		ASTM D-1000
<i>Temperature</i>	140° F	60° C	
<i>Storage Conditions</i>	Store in a clean, dry place at room temperature. Avoid temperature and humidity extremes.		

Important Notice: All properties are approximate and based on calculations and tests we believe to be reliable. However, the accuracy and completeness are not guaranteed. Before using, user shall determine the suitability of the product for its own use and assumes all risk and liability related to the product. The seller limits its obligations to replacement or at its option, reimbursement of the purchase price of products shown to the seller's satisfaction to have been defective at the time the seller sold it.

www.Qspac.com