



Product Data Sheet

- ✓ Direct printable on film surface with all leading brands of alcohol-based inks
- ✓ Great ink anchorage
- ✓ Excellent coating profile and tension control for smooth printing process
- ✓ For use on Siat L33, L36, L233 or equivalent flexo printing presses

United States Units

Metric Units

Test Method

Backing

Adhesive

Total Thickness

Film Thickness

Adhesive Thickness

Adhesion to Steel

Tensile Strength

Elongation

Service Temperature

Application Temperature

Storage Conditions

Store in a clean, dry place at room temperature.
Avoid temperature and humidity extremes.

Safety/Environmental Information:

MSDS Class:

Health:

Fire:

Reactivity:

VOC:

CONEG:

Hazard Ratings: 0 - Minimal, 1 - Slight, 2 - Moderate, 3 - Serious, 4 - Extreme

Does not contain any substances according to the Ozone Depleting Substances, 40 CFR Part 82 and the Safe Drinking Water Enforcement Act of 1986.

Important Notice: All properties are approximate and based on calculations and tests we believe to be reliable. However, the accuracy and completeness are not guaranteed. Before using, user shall determine the suitability of the product for its own use and assumes all risk and liability related to the product. The seller limits its obligations to replacement or at its option, reimbursement of the purchase price of products shown to the seller's satisfaction to have been defective at the time the seller sold it.

www.Qspac.com