



Impulse Sealer Specification

Item#	Total Max Seal Thickness	Max Seal Width	Heat Time (Second)	Watts	Amperage	Volage	Operation Bags
QPC-415-04	6mil	3.9"	0.2 - 1.3	160W	3.0	120	PE,PP,PVC
QPC-415-08	8mil	7.8"	0.2 - 1.3	260W	3.0	120	PE,PP,PVC
QPC-415-12	8mil	11.8"	0.2 - 1.3	380W	3.0	120	PE,PP,PVC
QPC-415-16	8mil	15.7"	0.2 - 1.3	600W	3.0	120	PE,PP,PVC
QPC-415-20	8mil	19.6"	0.2 - 1.3	730W	3.0	120	PE,PP,PVC
QPC-415-08C	8mil	7.8"	0.2 - 1.3	260W	3.0	120	PE,PP,PVC
QPC-415-12C	8mil	11.8"	0.2 - 1.3	380W	3.0	120	PE,PP,PVC
QPC-415-16C	8mil	15.7"	0.2 - 1.3	680W	3.0	120	PE,PP,PVC
QPC-415-20C	8mil	19.6"	0.2 - 1.3	730W	3.0	120	PE,PP,PVC
QPC-415-12F	16mil	11.8"	0.2 - 3.0	400W	3.8	120	PE,PP,PVC
QPC-415-18F	16mil	17.7"	0.2 - 3.0	600W	5.0	120	PE,PP,PVC
QPC-415-24F	16mil	23.6"	0.2 - 3.0	800W	6.3	120	PE,PP,PVC
QPC-415-18A	16mil	17.7"	0.2 - 1.4	600W	7.0	120	PE,PP,PVC
QPC-415-24A	16mil	23.6"	0.2 - 1.4	800W	7.0	120	PE,PP,PVC